



## PRODUCT DATA SHEET

### Product Description

A durable, quality, interior vinyl acrylic paint that can be used as a primer and as a top coat.

### Uses

Intended for use where a high hiding product is required. Intended for use on unpainted interior surfaces including gypsum board, and plaster. Suitable for application by brush, roller and spray.

### Technical data

Type: Vinyl Acrylic  
 Gloss: Flat  
 Standard Colour: White  
 Tint Range: As Required  
 Recommended Number Of Coats: 1  
 Theoretical Coverage: 350-400ft<sup>2</sup> per US gal @ 4mils wet  
 Ph: 8.5-8.8  
 Viscosity: 100-110 KU  
 Density: 11.5±0.1 lb/US gal  
 Volume Solids: 31.7±0.2%  
 Weight Solids: 50.2±0.2%  
 Volatile Organic Compounds (VOC Theoretical): <50 g/L

### Surface preparation

Surface contamination shall be removed by washing with an appropriate cleaner, rinsed thoroughly and allowed to dry. Any peeling paint shall be sanded. All glossy surfaces shall be sanded dull. Stains from water, smoke, grease, etc. shall be sealed with an appropriate primer/sealer. Clean all sanding dust as it will decrease adhesion. For drywall fill all cracks and nail holes with a patching compound and sand smooth. Any joint compound must be cured and sanded smooth. Clean all sanding dust. For masonry, concrete, cement and block all surfaces must be cured as per the supplier's recommendations. All form and release agents must be removed. Rough surfaces can be filled to provide a smooth surface. For plaster surfaces, bare plaster shall be cured and hard. For wood surfaces, any exposed wood shall be sanded to a fresh surface. Use a wood filler or putty to fill all holes/imperfections and sand smooth. Remove all sanding dust.

### Application & clean Up

Brush, roll or spray  
 Touch: 15-30 minutes  
 Recoat: 1-2 hours  
 Drying and recoat times are temperature, humidity and film thickness dependent.

### Miscellaneous information

If mildew is present, surface should be washed using a bleach solution. Apply solution and scrub area affected. Allow solution to remain for 10 minutes on surface and then rinse thoroughly with water. Allow surface to dry completely before painting.

Should not be used on previous coatings with gloss or semi-gloss finishes.