



PRODUCT DATA SHEET

Product Description

A durable acrylic, uniquely formulated to block stains from bleeding through the topcoat. It is formulated to seal stubborn stains that normally would continue to bleed through normal paint. These include stains caused by smoke damage, water staining, etc.

Uses

Recommended for use over a variety of substrates including new wood and plywood, drywall, masonry, Intended for use on unpainted surfaces including gypsum board, plaster, and smooth concrete. Suitable for application by brush, roller and spray.

Technical Data

Gloss: Flat
Colour: White
pH: 9.0-9.5
Viscosity: 93-98 KU
Density: 10.7±0.2 lb/US gal
Weight Solids: 49.2±0.1%
Volume Solids: 38.5±0.2%
VOC: 70 g/L

Theoretical Coverage: 350-400ft² per US gal @ 4mils wet (depending on porosity of surface and application method)

Surface Preparation

Surfaces must be clean and dry and free from dust, grease and other contaminants. All surface contamination shall be removed by washing with an appropriate cleaner, rinse thoroughly and allowed to dry. Any peeling paint shall be sanded. All glossy surfaces shall be sanded thoroughly. Clean all sanding dust as it will decrease adhesion. For drywall fill all cracks and nail holes with a patching compound and sand smooth. Any joint compound must be cured and sanded smooth. Clean all sanding dust.

For fire restoration it is extremely important to clean smoke damaged surfaces thoroughly with an appropriate cleaner before use.

Application & Clean Up

Paint only when air and surface temperatures are between 10°C - 30°C. Stir thoroughly before use and occasionally during use. Apply as supplied using a brush, roller or sprayer. Thinning with water will affect stain blocking properties and is not recommended. Multiple coats may be required for complete stainblocking and hide. Dry to touch within 30 mins and recoat time is 2hrs at 25°C and 50% relative humidity. Drying and recoat times are temperature, humidity and film thickness dependent.

Miscellaneous Information

If mildew is present, surface should be washed using a bleach solution. Apply solution and scrub area affected. Allow solution to remain for 10 minutes on surface and then rinse thoroughly with water. Allow surface to dry completely before painting.