



PRODUCT DATA SHEET

Product Description

A durable, quality, vinyl acrylic paint recommended for striping a variety of natural turf sports surfaces including grass, cinder, and dirt.

Technical data

Type: Vinyl Acrylic
 Gloss/Sheen: Flat
 Colour: White
 Density: 11.7±0.1 lbs/US gal
 Weight Solids: 53.1±0.2%
 VOC: <50 g/L
 Specific Gravity: 1.41

Recommended Coverage per Coat

Estimated Coverage: 300 lineal feet per US gal @ 5mils wet
 Actual coverage may vary depending on substrate, application method, waste, surface porosity and thinning.

Surface preparation

General Surface Preparation: Surfaces must be clean and dry and free from loose materials. Grass turf surfaces should be cut low prior to initial line application. Ensure air temperatures are above freezing and avoid frost, fog or wet conditions.

Application Conditions

Temperature: 10°C (50°F) minimum, 43°C (110°F) maximum, air/surface/material. At least 2.8°C (5°F) above dew point.
 Relative humidity: 85% maximum

Application Information

Stir paint thoroughly before use. Thinning of paint is dependent on the opacity required and the porosity and texture of the substrate. Thin with water as required. The hiding and durability of the paint will decrease with excessive thinning. A quality line marking machine is recommended; however, brush or roller application is possible. If brushing a polyester/nylon brush is recommended. If rolling a 3/8"-3/4" nap roller cover is recommended. For spray application a fluid pressure of 1500 to 2000PSI with a 0.011" to 0.015" orifice is recommended.

Clean Up

Immediately clean spills and splatters with soap and warm water. Clean hands and tools immediately after use with soap and warm water. After cleaning flush spray equipment with mineral spirits to stop rusting of the equipment. Follow manufacturer's safety guidelines when using mineral spirits.